



VISORJET

VisorJet Smart PTZ



IP cameras VisorJet Smart PTZ

Model: VJS-P612-5

5 MP
+
30^{f/sec}

Resolution 5 MP
with frame rate
up to 30 fps

Smart
PTZ

Up to 260 preset
turntable positions

ONVIF 2.6
(PROFILE S)

ONVIF 2.6 (PROFILE S)
compatible

TRIPPLE
STREAM

Simultaneous broadcast
of three video streams

H.264
H.265

Support for H.264/H.265
codecs

12x

12x optical zoom



On-device analytics

SNMP

SNMP protocol support

SIP

SIP protocol support

Technical specification

Параметр	Value
Parameter	VJS-P612-5
Video matrix	1/2.8
Frame rate	30 fps
Max. Image Resolution	2592x1944
Focal length	5.3-64 mm, 12X Optical Zoom
IR illumination range, m	100
IR wavelength, nm	850
Sensitivity, lx	0.005 (F1.2, AGC вкл.), 0 с ИК
Signal-to-noise ratio, dB, min	120
Video compression algorithm	H.265+ / H.265 (HEVC) / H.264+ / H.264 / MJPEG
Frame rate (main stream)	30 fps (2592x1944, 2592x1520, 2048x1536, 1920x1080, 1280x960, 1280x720, 704x576)
Frame rate (second stream)	30 fps (704x576, 640x480, 640x360, 352x288, 320x240, 320x192, 320x176)
Frame rate (third stream)	30 fps (1920x1080, 1280x720, 704x576, 640x480, 640x360, 352x288, 320x240, 320x192, 320x176)
Video stream	RTSP, ONVIF supported (Profile S)
Supported network protocols	IPv4/IPv6, TCP, UDP, RTP, RTSP, RTCP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, SMTP, UPnP, SIP, SNMP, PPPoE, VLAN, 802.1x, QoS, IGMP, ICMP, SSL
Audio stream	No
Power supply	PoE (802.3af) / 12 V \pm 10 % DC
Power consumption, W, max	20 (when IR illumination on)
Dimensions, mm	160 x 274 x 210
Weight, g	2000
Body material	Metal, plastic
Controlled digital I / O	1/1
External audio port I / O	—